

Model 290 UHF Datalink Transponder

35 Hill Ave Fort Walton Beach FL 32548 | PH: 1-888-325-9422 | Fax: 1-850-243-1378 | www.gomicrosystems.com



Features

- Field Proven Hardware
- Modular Design
- 16 Available Frequency Channels in the range of 380 MHz to 450 MHz
- GMSK Modulation
- Greater than 3W RF Output Power
- 3 antenna ports
- Ruggedized Aluminum Chassis

Applications

- Autopilot Interface
- Command and Telemetry

Description

The Model 290 UHF datalink transponder is a command receiver, digital command decoder, digital telemetry encoder, telemetry transmitter, and target interface enclosed in a single lightweight package. The transponder receives commands transmitted by the ground control station and interfaces with the vehicle management computer or autopilot.

Uplink UHF command messages from the ground control station are received by the transponder in the frequency band of 380 MHz to 435 MHz. The RF data is converted to a serial data stream that is digitally transmitted to the vehicle autopilot for processing. The autopilot can then send a serial data stream back to the transponder where the telemetry downlink is then transmitted down to the ground control station. It also has three antenna ports to support multiple antenna inputs via the vehicle RF switch. Multiple antenna inputs can be toggled through for the strongest signal.

The Model 290 has been qualified per MIL-STD-461 (EMI), MIL-STD-810 (Environmental), MIL-HDBK-781 (Reliability) making it one of the most capable devices in the industry.

Technical Specifications

AS9100C and ISO 9001:2008 Certified

Characteristics

- **Frequency:** Model 290-1: 435 MHz to 450 MHz | Model 290-2: 380 MHz to 400 MHz
- **Channels:** 16
- **Channel Bandwidth:** 25 kHz
- **Occupied Bandwidth:** 20 kHz
- **Modulation:** GMSK
- **Burst Data Rate:** 14.4 kbps
- **Power Output:** Greater than 3 Watts
- **Maximum PRF:** 10 Hz

UHF Receiver

- **Sensitivity:** -100 dBm @ 1×10^{-4} BER
- **Selectivity:** -60 dBm @ 12.5 kHz
- **Spurious Rejection:** -70 dB

Environmental (MIL-STD-810) / EMI (MIL-STD-461D)

- **Temperature:** Operating: -40°C to +71°C
- **Vibration:** Random, 15 to 2000 Hz, 9.3 G 30 minutes per orthogonal axis
- **Altitude:** 50,000 ft
- **Shock:** Sawtooth, 20 G for 11ms, 18 shocks total
- **Humidity:** Up to 95% @ 40°C (all boards are conformal coated)
- **EMI/RFI:** Certified to MIL-STD-461D, Class A1

Power Requirements

- **DC Power:** 22 VDC to 32 VDC (28 VDC Nominal)
- **Reverse Polarity:** Yes
- **Power Consumption:** 55 Watts maximum (1.8 amps @ 28 VDC)

Physical

- **Size:** 5.00" W x 2.95" T x 6.00" D
- **Weight:** 6 pounds
- **Connectors:** Circular, SMA Female
- **Finish:** Black Paint
- **Installation:** Flange Mount Base Plate

Contact us for custom modifications

For additional information contact:

Micro Systems, Inc.
35 Hill Ave
Fort Walton Beach, FL 32547
PH: 1-888-325-9422
FAX: 1-850-243-1378
www.gomicrosystems.com



a **KRATOS** company

© 2010 Micro Systems, Inc
Specifications subject to change without notice