MANT-1424-2C
Broad Beam Width Dual Polarized Low Gain Antenna System

This is a totally integrated system where the antenna is hard mounted to the electronic package and the RF Output of the amplifiers can be used as an Input to Receivers, Multicouplers or Down Converters. The Noise Figure at the RF Input Connector is 1.7 dB Maximum and 1.4 dB Typical.

Antenna Specifications

Antenna Frequency Range:	1,435 to 2,400 MHz
Antenna Gain:	
	- 1,485 MHz 6.5 dBic, Typical
	- 1,800 MHz 8.0 dBic, Typical
	- 2,300 MHz 9.0 dBic, Typical
Antenna 3 dB Beam width:	
	- 1,485 MHz 70 degrees, Typical
	- 1,800 MHz 60 degrees, Typical
	- 2,300 MHz 50 degrees, Typical
Antenna Polarization:	RHCP and LHCP
Axial Ratio:	2 dB
V.S.W.R.:	2.0:1

Low Noise Pre-Amplifier (2 each)

Pass band:	1,435 to 2,400 MHz
Gain:	45 dB, Typical
Noise Figure:	1.0 dB, Maximum, 0.8 dB, Typical

System Packaging

AC Power:	Standard: **90 to 260 VAC @ 50-60 Hz**
Power Connector:	MS3102E10SL-3P
Display:	LED showing Power to system
RF Connectors:	Type N-female
Mounting:	Tripod ready with an additional 1 ¼" x 6 " Extension for additional length from bottom of chassis
Chassis:	Weatherproof and Sealed
Operating Temperature Range:	-20 to +50 degrees C.
Humidity:	5 to 95 % Non Condensing


MU-DEL
ELECTRONICS, INC
MANASSAS, VIRGINIA 20109
PN MANT-1424-2C-1
SN 765302
MADE IN USA